

Material	
Components	PVC+stone composed core with PVC decoration paper and wearlayer
Finishing	UV coating,micro-beveled, 1mm IXPE underlayer
Click System	Unilin
Length	60 inches (1524mm)
Width	8.976 inches (228mm)
Thickness	0.315 inches (8mm)
Wear Layer	0.5mm
Backlayer IXPE	1.5mm
Carton	5 boards=18.7 sq ft
Pallet	45 CTNS= 841.55 sq ft
Product Characteristic	
Lipping	≤0,2 mm
Squareness	≤0.3mm
Joint Gap	≤0.25mm
Dimensional Stability	80°C*6h ≤=0.18% (ISO 23999,ASTM F3261)
Heating Warpage	80°C*6h ≤=1.8mm (ISO 23999,ASTM F3261)
Peel Strength	≥70N/50mm
Locking Strength	1.6KN/m (ISO10582)
Physical and Chemical Properties	
Reaction to fire	Bf1 - S1
Emission of Formaldehyde	E1
Wear Resistance	≥4000round(EN 13329,S-42)
Others	
Product Marking	CE
Usage (Interior or exterior)	Interior only
Installation	Click Locked (Referred to installation instruction)
Accessories:	Skirting T-molding, etc.
Maintenance:	Water Resistance, Normal Wet Mopping Cleaning, no waxing or oil needed